



TRITON AND TRITON TOWER HARNESS



TRITON HARNESS CONFIGURATIONS

TRITON HARNESS

The **NEW TRITON** harness is an innovative design featuring superior comfort, versatility and durability. The TRITON harness offers:

- extremely lightweight and durable design that reduces worker fatigue while extending the products life.
- a four-motion leg pivot point. The improved design increases comfort during climbing, suspension and work positioning.
- a breathable waist pad providing the highest level of comfort and functionality.
- easy to use webbing adjusters: Securing the harness without slippage. Excess webbing is no longer an issue with the elastic keeper system.
- a removable Suspension Seat (TRITON TOWER): Comfortable padding allow for long term suspension and rigid aluminum seat board providing support and stability. Durable steel positioning rings.
- a removable waist belt to secure tool pouches and holders. Velcro straps secure the belt in place, preventing tool pouches from coming loose.
- optional shoulder and leg pads that can be added for additional comfort while climbing or hanging in the harness.
- Aluminum & Stainless Steel hardware: Lightweight and durable hardware reduces worker fatigue and increases product life.

AVAILABLE MODELS



TRITON HARNESS

art no G-US-1163-SIZE

harness only



TRITON TOWER HARNESS

art no G-US-1163-T-SIZE

includes harness, shoulder pads, and removable suspension seat*

AVAILABLE ACCESSORIES

SHOULDER PADS

- optimal comfort through breathable padding
- removable and washable



art no ACS-0302-1

XS/M

ACS-0302-2

M/XXL & XXL/5XL

LEG PADS

- optimal comfort through breathable padding
- removable and washable



art no ACS-0303-1

XS/M

ACS-0303-2

M/XXL

ACS-0303-3

XXL/5XL

SKYBOARD TOWER PRO

The new work seat for rope-supported tasks. Now even lighter, more compact and more comfortable thanks to the aluminum support wide plate. Individually adjustable.



art no G-US-0206

Work seat

G-US-0206-XL

LANY PARK

This ring is designed to hang fasteners in it when they are not in use. It can be attached to the belt by means of a Velcro fastener.

- easy to attach to the belt
- provides space for fasteners while not in use



art no ACS-0190

Parking rings

GENERAL

Standards

ANSI/ASSP Z359.11-2021, CSA Z259.10:2018 and OSHA

Features

Color	black/ orange
Fall indicator	yes
Tongue buckle gear belt	yes
Click buckles	yes
Lanyard Parking Rings	yes
Gear loop	yes

Back support	yes
Shoulder or leg padding	optional
Max. service life	10 years
Rated load	310 lbs (141 kg)
Attachment points	dorsal attachment point, sternal attachment point, side positioning rings

Dimensions

Size	XS/M	M/XXL	XXL/5XL
Waist size	25" - 45"	31" - 51"	37" - 57"
Weight	G-US-1163 G-US-1163-T	5.1 lbs (2.31 kg) 8.2 lbs (3.72 kg)	

Material

Webbing material	Polyester
Harness attachment points material	Aluminum
Material click buckle	Steel



SKYLOTEC North America LP
2300 E. 77th Ave., Suite 100
Denver, CO 80229 USA
USA

Phone 1-303-544-2120
Fax 1-303-544-2122

E- Mail: ordersna@skylotec.de
www.skylotec.com

