

Data sheet
PEANUT Y



GENERAL

Art. no.:	HSG-022-2,5-6	E-class number:	40-02-01-03
EAN:	4030281183471	Customs no.:	84798997
Standard:	EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2020 RFU PPE- R/11.124:2020		

Data sheet

PEANUT Y

The compact connecting device PEANUT Y with the FS64 AL OR karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the drop height is extremely low. The FS64 AL OR GR with an opening width of 64 mm is light and yet very robust with a reinforced gate. The lanyard is perfectly suited for continuous, mutual securing - even at lower heights. The PEANUT Y is edge-suitable and thus also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 2.5 m long arms, the PEANUT Y is ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Colour:	orange / black / grey
Fall indicator	
Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND

DIMENSIONS

Size:	2,5m
Weight:	3,32 kg

HARDWARE

Carabiner on anchoring point side:

FS 64 ALU

Carabiner on belt side: KOBRA AL TRI

MATERIAL

Material:

Polyester, Polyamide, Aluminium
