

Data sheet
MILAN 2.0



GENERAL

Art. no.:	A-027	E-class number:	40-02-01-06
EAN:	4030281155843	Customs no.:	84251900
Standard:	DIN EN 341-1A:2011		

Data sheet

MILAN 2.0

MILAN is THE industrial standard evacuation device worldwide. The centrifugally controlled brake maintains a constant descent speed of 0.9 m/s, thus ensuring fast and safe evacuation. The ultra-robust housing made in Germany is CNC-milled from a solid block aluminium.

- suitable for 2-person use and for alternating abseiling
- abseiling heights up to 500 m
- rescue operations of any kind at any place

With special [SEAL PACs](<https://bit.ly/3408bTx>) an extended lifetime of up to 15 years can be guaranteed, which can even be doubled once within a resealing process to 30 years.

Note: When working at heights, a suitable rescue concept based on a risk assessment is essential. MILAN offers a variety of applications for different rescue scenarios. To master these techniques, the user must be carefully trained by a SKYLOTEC-certified instructor who has been specially trained on the device.

GENERAL

Internat. standard:
ANSI Z359.4:2013, MEETS CSA Z259.2.3-1B:2012

FEATURES

Colour:	orange / black / white
Abseiling speed:	0,90 m/s
Abseiling height:	500,00 m
Max. service life:	20 Years
Max. number of persons:	2
Rated load:	260 KG
Temperature:	from 60 °C to -35 °C
Suspension element:	KM9

DIMENSIONS

Weight:	2,31 kg
---------	---------

HARDWARE

Carabiner on anchoring point side:
KOBRA TW

MATERIAL

Material:
Aluminium, Steel, Polyamide
