

Data sheet

ERGOGRIP SK16



GENERAL

Art. no.:	L-0368-1,8	E-class number:	40-02-01-90
EAN:	4030281160410	Customs no.:	56090000
Standard:	EN 358:2018		

Data sheet

ERGOG RIP SK16

The ERGOG RIP SK16 is a work positioning lanyard, which can be adjusted in length by using the runner. An FS 64 aluminum carabiner with a maximum gate opening of 64 mm is attached to the rope, and an STEEL D TRI carabiner is attached to the runner. The core sheath rope is extremely edge resistant, abrasion resistant and remains soft even when it gets wet, so that a long lifetime can be guaranteed. In addition, the ERGOG RIP SK16 can be easily adjusted with one hand.

[VIDEO1](http://www.skylotec.com/media/content/images/PDF/ERGOG RIP_A.mov)

[VIDEO2](http://www.skylotec.com/media/content/images/PDF/ERGOG RIP_B.mov)

GENERAL

Internat. standard:

ANSI/ASSP Z359.3-2019, MEETS CSA Z259.11-17 CLASS F

FEATURES

Colour:	white
Diameter:	16,00 mm
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	140 KG
Temperature:	from 45 °C to -35 °C
Suspension element:	KM16

DIMENSIONS

Size:	1,8m
Weight:	1,89 kg

HARDWARE

Carabiner on device:	STEEL D TRI
Carabiner on rope:	STEEL D TRI

MATERIAL

Material:	
Polyamide, Steel, Aluminium	
Rope material:	Polyamide