

DATASHEET

HMS DOUBLE TRI 2.0



GENERAL

Art.Nr:	H-206	Standards:	EN 12275-H:2013, EN 362-B:2004, UIAA 121: 2018
GTIN:	4030281303770	Net weight:	0.08 kg
E-class number:	40-02-01-05	Gross weight:	0.08 kg
Customs tariff number:	76169990		

DATASHEET

HMS DOUBLE TRI 2.0

HMS carabiner with DOUBLE TRIPLE gate. With the DOUBLE Gate with patented 180 ° technology, the locking sleeve can be turned in two directions. So the carabiner is equally easy to use for left and right-handers. - HMS carabiner with wide top bar to offer plenty of space for equipment (e.g. ropes, slings, etc.) - Patented double gate usable by both left- and right-handers - I-Profile spine to optimize strength / weight ratio - Wider cross-sections at the points exposed to abrasion (apex /crown and base) - Compact Key-Lock nose and wide gate opening for snag-free attaching / detaching to fixation points

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Arborists, RBA rigging, Via ferrata, Sport climbing, Alpine climbing, Alpine tours, High ropes courses
Fallindicator:	No
Colour:	polyethylene_terephthalate, Grey
Strengths - lengthways:	25.00 kN
Strengths - open:	7.00 kN
Strengths - across:	7.00 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 362: 2004), Type H (EN 12275:2013)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No
Standard UIAA:	Yes
Anti-twist device:	No
Carabiner clasp:	Double-Triple

DIMENSIONS

Opening width:	24 mm
Working load limit:	250.00 kg

MATERIAL

DATASHEET

HMS DOUBLE TRI 2.0

Material: Aluminium
